


3M™ Pleated Foil Shielded Cable

.025" 30 AWG Solid, TPE Primary, TPE Cover

90201 Series



- Can be used with IDC mass termination connectors
- Can be used in applications requiring standard impedance of 100 Ω balanced (differential)
- Extremely low crosstalk, used in the all signal mode to quadruple signal density as compared to standard .050 inch flat ribbon cable
- Perfect for board-to-board applications within electronic equipment, TPE covering prevents pleated copper foil from accidental shorting
- Solid pleated copper foil provides flexibility and 35 db average shielding effectiveness

Date Modified: May 30, 2003

TS-0402-14
Sheet 1 of 2

Physical

Cover



Material: Thermoplastic Elastomer (TPE)

Color: Gray

Primary Material: Thermoplastic Elastomer (TPE)

Marking

Standard: None

Canadian Option:  AWM 20674 105C 150V VW1 3M NU  AWM IA 105C 150V FT1 EU <50V

Conductors: 30 AWG [0.254] Tinned Solid Copper

Shielding: Solid, Pleated, Copper Foil

Electrical

Voltage Rating:	USA: 150V	Canada: 150V	EU: <50V
Insulation Resistance:	(Primary Cable) $> 1 \times 10^{10} \Omega/10 \text{ ft. [3m]}$		
	Unbalanced	Balanced	
Characteristic Impedance:	53 Ω	104 Ω	
Capacitance:	28.4 pF/ft (93.2 pF/m)	14.5 pF/ft (47.6 pF/m)	
Inductance:	.08 $\mu\text{H/ft}$ (0.26 $\mu\text{H/m}$)	.16 $\mu\text{H/ft}$ (0.52 $\mu\text{H/m}$)	
Propagation Delay:	1.52 ns/ft (4.99 ns/m)	1.51 ns/ft (4.95 ns/m)	
Velocity of Propagation:	67%	67%	

Note: Unbalanced is measured between ground-signal-ground conductors with shield grounded. Balanced is measured between signal conductors within a pair, with the shield floating.

Environmental

Temperature Rating: -20°C TO +105°C

Flammability Rating: USA: VW-1

Canada: FT1

UL File No.: E42769, Style No.: 20674



Interconnect Solutions

<http://www.3M.com/interconnects/>

3M is a trademark of 3M Company.

For technical, sales or ordering information call


800-225-5373

3M™ Pleated Foil Shielded Cable

.025" 30 AWG Solid, TPE Primary, TPE Cover

90201 Series

Number of Conductors	3M Part Number	Dimension A ± .04	Dimension B
20	90201/20	0.54 [13.7]	0.475 ± .006 [12.06]
26	90201/26	0.69 [17.5]	0.625 ± .006 [15.88]
36	90201/36	0.94 [23.9]	0.875 ± .009 [22.23]
40	90201/40	1.04 [26.4]	0.975 ± .009 [24.77]
50	90201/50	1.29 [32.8]	1.225 ± .009 [31.11]
60	90201/60	1.54 [39.1]	1.475 ± .012 [37.47]
68	90201/68	1.74 [44.2]	1.675 ± .012 [42.55]
80	90201/80	2.04 [51.8]	1.975 ± .015 [50.17]
100	90201/100	2.54 [64.5]	2.475 ± .017 [62.87]



Inch
[mm]

Tolerance Unless Noted			
	.0	.00	.000
Inch	±.1	±.05	±.010

Note: Blue marking on edge of primary cable designates wire #1.

[] Dimensions for Reference only

Ordering Information

90201/XXX

Blank = Standard
C = CSA Certified Version

Number of Conductors
(See Table)

Note: Standard length is 100 ft/roll.

TS-0402-14
Sheet 2 of 2

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.



Electronic and Interconnect Solutions Division

6801 River Place Blvd.
Austin, TX 78726-9000
www.3M.com/eisd

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of 1 year from the date of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.**